

SPECIFICATION OF ELECTRIC SUBMERCIBLE PUMPS FOR PR-3600002222.

SL. NO	ITEM CODE	DESCRIPTION	POWER SUPPLY	TYPE OF CASING AND SEALS	SIZE OF OUTLET HOSE	LENGTH OF POWER CABLE	QUANTITY NOS
1	1000076534	Vertical bottom suction type Electric submersible dewatering pump - 10HP / 7.5 KW-3PH with Power Cable of 20 mtrs length and Flame proof motor with Control panel suitable for 10 HP/7.5KW/3PH, Overload Relay and meter Encloser.	10 HP / 7.5 KW 3PH-50Hz-415V, AC supply	Stator Insulation Class "H" Aluminium Alloy Outer Casing, 100mm Hose Outlet in SS, DoubleTC/TC and TC/TC Mechanical seals, 410 SS Hardned Impeller , SS 431 Shaft,SS 304 Strainer & Hardware	100mm Hose Outlet in SS	20 METRE	5
2	1000106433	Vertical bottom suction type Electric submersible dewatering pump-3HP / 2.2KW-1PH with Power Cable of 20 mtrs length and Flame proof motor with Control panel suitable for 3HP/2.2KW/1PH, Overload Relay and meter Encloser.	3 HP / 2.2KW 1PH-50Hz-230V, AC supply	Stator Insulation Class "H" Aluminium Alloy Outer Casing, 75mm Hose Outlet in SS, DoubleTC/TC and TC/TC Mechanical seals, 410 SS Hardned Impeller , SS 431 Shaft,SS 304 Strainer & Hardware	75mm Hose Outlet in SS	20 METRE	5

✓
 CA-SUBM
 10/29/2024
 11/12/2024