

Bid Document

| Bid Details | |
|--|--|
| Bid End Date/Time | 12-01-2019 20:00:00 |
| Bid Life Cycle (From Publish Date) | 90 (Days) |
| Bid Offer Validity (From End Date) | 75 (Days) |
| Ministry/State Name | Madhya Pradesh |
| Department Name | Energy Department Madhya Pradesh |
| Organisation Name | Madhya Pradesh Poorv Kshetra Vidyut Vitran Company Limited (mppkvcl) |
| Office Name | Jabalpur |
| Total Quantity | 40 |
| Item Category | revolving chair , chairs-office |
| MSE Exemption For Years Of Experience And Turnover | Yes |

Revolving Chair (12)

Technical Specifications

[* As per GeM Category Specification](#)

| Specification | Specification Name | Values | Allowed Values |
|---------------|---|--|---|
| GENERAL | Chair Type | central tilt | * |
| | Tilt Tension Adjustment | No | * |
| | Height Adjustment \pm 5(mm) | up to 120 mm | up to 100 mm, up to 120 mm, N.A, up to 90 mm, up to 65 mm |
| | Arm | With | With, Without |
| | Type of backrest support | backrest symmetrical lumber support | backrest with lumber support of polypropylene at multilevel across back, backrest symmetrical lumber support, Backrest With Adjustable Lumber Support |

| | | | |
|----------|--|--|---|
| | Arm Type | Fixed | Adjustable, Fixed, NA |
| | Colour of Fabric for Seat and Backrest | black | * |
| | Ergonomic Seat Design | Yes | Yes, No |
| | Back type | fixed | push back, fixed, height adjustable |
| | backrest has separate adjustable headrest | No | Yes, No |
| | Seat type | fixed | fixed, sliding |
| | Seat is curved | No | * |
| | Locking mechanism | No | * |
| | Type of locking | N.A | * |
| | Number of arm movement | N.A | 2(up & down), 4(up & down end left & right), 6(Up & Down,Left & Right And Swivel), 8(Up & Down,Left & Right,Swivel And Front & Back), N.A |
| | Lumber support | N.A | integrated, external & fixed, external & adjustable, N.A |
| MATERIAL | Pedestal Base | ABS Plastic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size | Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm Size, ABS Plastic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Electro Coated with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Stainless Steel with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium Die Cast with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium Die Cast Chrome Finish With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, , Nylon Base With Nylon Twin Caster Wheels |

| | | |
|--|----------------------------------|---|
| | | Minimum Of 50-70 Mm Diameter, Aluminium Alloy With Nylon Twin Caster Wheels Minimum Of 50-70 Diameter, Wooden Cladded With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Chrome finish with 5 wheels |
| Arm Material | steel covered with polyurethane | steel covered with polyurethane, pu foam bonded chrome coted, aluminium covered with pu, CRCA pipe with foam, 19 mm (+/- 2 mm) ROUND pipe with cushion, 19 mm (+/- 2 mm) round SS pipe with cushion, Proppylene, Steel covered with polypropelene, Steel Covered with Wooden Cladding, WITHOUT ARM |
| seat material | PU foam covered with mesh fabric | pressed and moulded plywood with polypropylene cover, PU foam covered with mesh fabric, PU Foam covered with Fabric, PU Foam Covered With pure leather, PU Foam Covered With pure leatherite |
| Density of PU foam used in seat KG per Cu Meter (+/- 3) | 40 | * |
| Density of PU foam used in backrest in KG per Cu Meter (+/- 3) | 40 | * |
| Material of Fabric Back Cover | N.A | mesh fabric, Inner frame Upholstered with Mesh fabric and mounted on main assembly, pure leather, 100% polyester fabric, nylon with poly olefin elastomer, Leatherite, N.A |
| Material of Fabric of Seat Cover | N.A | foam laminated mesh fabrics, Mesh Fabrics, |

| | | | |
|---------------|---|--|--|
| | | | pure leather, leatherite, 100% polyester fabric, N.A |
| | GSM/Thickness of fabric ±5%(Gram/Square meter) | N.A | * |
| DIMENSION | Overall Chair Height ±15mm | 1125 | * |
| | Backrest Height ±15mm | 520.0 | * |
| | Backrest Width ±10mm | 480.0 | * |
| | Seat Height ±15 mm | 500 | 420, 450, 480, 500, 520 |
| | Seat Width ±10 mm | 520 | 440, 480, 500, 520, 550, 460, 360 |
| | Seat Depth ±10 mm | 520.0 | 400, 460, 480, 500, 520, 550, 420, 440, 540, 360 |
| | Thickness of M S Plate Joining the under structure with Seat | 0.5 | * |
| | Thickness of Plywood used in Seat ±1(mm) | 12 mm | 12 mm, 15 mm, 18 mm, N.A |
| | Thickness of Plywood used in Backrest ± 1(mm) | 12 mm | 12 mm, 15 mm, 18 mm, N.A |
| | Padestal Size (Diameter in mm) +/- 10 mm | Nylon Base With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter | * |
| | Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm) | 25 mm | * |
| | Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM) | 25 mm | * |
| WARANTEE | Warrantee period in number of years | 1-year | 1-year |
| CERTIFICATION | Test reports to be furnished to buyer on demand | YES | YES, NO |
| | BIFMA Certification | NO | YES, NO |
| | OEM of offered | NO | YES, NO |

| | | | |
|--|---|----|---------|
| | product is ISO 9001:2015 certified | | |
| | OEM of offered product is ISO 14001:2015 certified | NO | YES, NO |
| | OEM of offered product is ISO 18001:2007 certified | NO | YES, NO |
| | Green guard certification | NO | YES, NO |
| | Aiota | NO | YES, NO |

* Bold specifications are the golden parameters.

Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address | Quantity | Delivery Days |
|-------|-----------------------------|--|----------|---------------|
| 1 | Ramesh Chandra Sahu | 482008,O/o EE (Area Store), Nayagaon, Rampur, MPPKVCL, Jabalpur, | 12 | 15 |

Chairs-office (28)

Technical Specifications

[* As per GeM Category Specification](#)

| Specification | Specification Name | Values | Allowed Values |
|---------------|---|-------------------------------|---|
| GENERIC | Conformity to Indian Standard IS 3499 (Part-1) Latest | Yes | * |
| | Chair Type | With Arms | With Arms, Without Arms |
| | Type of Seat and Backrest | Padded with Polyurethane Foam | Made of Polythene cane, Padded with Polyurethane Foam, moulded plywood, injection moulded Polypropylene, Seat made of padded with polyurethane foam and Backrest made of Mesh with support of injection moulded polypropylene |
| | Frame Type | Cantilever | Cantilever, 4 Legs |
| | Castors | Without | With, Without |

| | | | |
|----------|--|--------------------------------|---|
| MATERIAL | Type of Wood used in Polythene cane Chair | solid wood | solid wood, teak wood, hot pressed board, plastic net, NOT APPLICABLE |
| | Material of Fabric Back Cover | N.A | knitted with cane, leather foam, plastic net, leather, leatherite, polyster, N.A |
| | Thickness of Plywood used in Backrest IN MM (± 1 mm) | 35 mm | 12 mm, 15 mm, 18 mm, 20 mm, 25 mm, 30 mm, 35 mm, 40 mm, N.A |
| | Frame Material | chrome on MS | MS, wood, CRCA ERW round pipe, ERW pipe, CRCA pipe with wooden sheet, STAINLESS STEEL, STAINLESS STEEL 304, STAINLESS STEEL 202, chrome on MS |
| | Density of Polyurethane Foam Used in Seat ± 2 (Kg/Cub M) | N.A | * |
| | Material of Fabric of Seat Cover | fabric | black leatherite, leather foam, plastic net, knitted with cane, fabric, polyurathane, N.A |
| | Density of Polyurethane Foam Used in Backrest ± 2 (Kg/Cub M) | N.A | * |
| | Thickness of Plywood used in Seat ± 1(mm) | 35 mm | 12 mm, 18 mm, 20 mm, 25 mm, 30 mm, 35 mm, 40 mm, N.A |
| | GSM/Thickness of Fabric ± 5 (Gram per Sq Meter) | N.A | 80 Gram per Sq Meter, 220 Gram per Sq Meter, 250 Gram per Sq Meter, 290 Gram per Sq Meter, N.A |
| | Arm Material | Polyurethane padded on Plastic | * |
| | Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 3 mm) | N.A | 25 mm, 50 mm, 62 mm, 65 mm, 70 mm, N.A, 40 mm |
| | Thickness of Polyurethane Foam Used in Seat IN MM (+/- 3 mm) | 15 mm | 15 mm, 20 mm, 25 mm, 30 mm, 40 mm, 50 mm, 60 mm, 70 mm, 75 mm, 80 mm |

| | | | |
|-----------------|--|-------------------------|---|
| | Shoe Type | Polypropylene | * |
| DIMENSION | Size of Material (mm) | 16 SWG 30 mm round pipe | 14 SWG 25 mm round pipe, 16 SWG 30 mm round pipe, 2 mm thick 25 mm tube, 40 mm teak wood, 16 gauge tubular pipe |
| | Chair Height ±15(mm) | 950 mm | 700 mm, 750 mm, 800 mm, 830 mm, 850 mm, 890 mm, 950 mm, 1000 mm, 1050 mm, 1100 mm |
| | Seat Depth ±10(mm) | 500 mm | * |
| | Seat Width ±10 (mm) | 600 mm | 350 mm, 380 mm, 400 mm, 450 mm, 470 mm, 500 mm, 550 mm, 600 mm, 650 mm, 520 MM |
| | Seat Height IN MM ±5(mm) | 460 | 400, 430, 460, 480, 500, 380 |
| | Backrest Width ±10(mm) | 450 mm | 350 mm, 380 mm, 400 mm, 430 mm, 450 mm, 500 mm, 550 mm, 480 mm |
| | Backrest Height ±10(mm) | 750 mm | * |
| | Arm Length ±5(mm) | N.A | 200 mm, 250 mm, 300 mm, 350 mm, 400 mm, 450 mm, N.A, 470 mm, 490 mm |
| | Arm Width ±2(mm) | N.A | 25 mm, 30 mm, 40 mm, 50 mm, 60 mm, 70 mm, 75 mm, N.A |
| COLOUR & FINISH | Colour of Fabric for Seat and Backrest | black | * |
| | Paint Type | epoxy polyster | chrome, epoxy polyster, polished, synthetic enamel, powder coated on MS, N.A |
| | Colour of Paint | NA | * |
| CERTIFICATION | Polythene cane conforming to Type-1 of IS 5378 /1994 | YES | * |
| | Test reports to be furnished to buyer on demand | YES | YES, NO |
| | BIFMA certification | YES | YES, NO |
| | OEM of offered product is ISO | YES | YES, NO |

| | | | |
|----------|---|-----|---------------|
| | 9001:2015 certified | | |
| | OEM of offered product is ISO 14001:2015 certified | YES | YES, NO |
| | OEM of offered product is ISO 18001:2007 certified | YES | YES, NO |
| WARRANTY | Warranty period in number of years | 1 | 1, 2, 3, 4, 5 |

* Bold specifications are the golden parameters.

Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address | Quantity | Delivery Days |
|-------|-----------------------------|--|----------|---------------|
| 1 | Ramesh Chandra Sahu | 482008,O/o EE (Area Store), Nayagaon, Rampur, MPPKVCL, Jabalpur, | 28 | 15 |

EMD Detail

| | |
|----------|----|
| Required | No |
|----------|----|

ePBG Detail

| | |
|----------|----|
| Required | No |
|----------|----|

Splitting

Bid splitting not applied.

Buyer Specific Additional Terms and Conditions

1. **Scope of supply (Bid price to include all cost components) :** Only supply of Goods

[This Bid is also governed by the General Terms and Conditions](#)

---Thank You---